



**DEXTER**  
LAUNDRY

## On-Premise Magnum-Load T-1200 Washer

(Model WCVD75HCS-12)



## On-Premise Magnum-Load T-1200 Washer

Dexter washers are engineered for the laundry owner demanding greater efficiency, performance, and programming capabilities.

### Durable Design

- **Save water** with “sump free” design
- **304 Stainless Steel cylinder, outer tub, top, front, and side panels** keep Dexter washers looking good
- **Heavy-duty Sur-Coat Frame** is built like a battleship to last a lifetime
- **Over-sized bearings and seals** run smooth and add to machine life

### VFD Technology

- **Reduce installation cost** by using single or three phase power
- **Extend motor life** by ramping current inrush
- **Save electricity** with lower running amperage draw
- **Lower electricity demand** by eliminating spike usage

### 100 G-Force Extraction

- **Save drying energy** with 100 G-Force washers that remove more water
- **Enhance customer turnover** with better washer and dryer performance
- **Achieve consistent results** throughout all washer sizes

### Powerful Controls

- **Palm OS®** with built-in infrared port
- **Save programming time** using a handheld computer running optional Palm OS® software
- **Easily customize** cycles, water temperatures, supply inputs and more

### Customer Friendly Design

- **Large, easy to use door** for convenient loading and unloading
- **Easily connected** to automatic supply injection systems
- **Easy-to-read digital display** including cycle time remaining information
- **Soft touch cycle selection buttons** with temperature icons
- **Ultra-quiet machine operation** improves the laundry environment



# T-1200 OPL Washer Specifications

## CAPACITY

Load Size	Magnum Load	
Dry Weight Capacity	75 - 80 lbs.	33.8 kg
Cylinder Diameter	30"	76.2 cm
Cylinder Depth	28"	71.2 cm
Cylinder Volume	11.5 cu ft	326 dm <sup>3</sup>

## DIMENSIONS

Cabinet Height	58"	147.30 cm
Cabinet Width	34.39"	87.31 cm
Overall Depth	45.25"	114.94 cm
Floor to Door Bottom	20.5"	52.07 cm
Door Opening	15.25"	38.74 cm

## WASHING/EXTRACTION

High Extract Speed	100 G-Force	485 RPM
Intermediate Extract Speed	60 G-Force	375 RPM
Washing Speed	43 RPM	
Motor Size	3 HP	2.24 Kw

## ELECTRICAL

Electrical Phase	Single or Three
Electrical Voltage (60 Hz)	208-240 volts
Electrical Running (Amps)	8.4
Circuit Protection (Amps)	20 amp
Electrical Wire Size	12 gauge
Electrical Service (Single Phase)	2 wire + ground
Electrical Service (Three Phase)	3 wire + ground

## WATER

Average Water Usage	88 gal	332.64 L
Maximum Hot Water Usage	39 gal	147.42 L
Water Inlet Size	3/4"	19mm
Water Flow Rate (per minute)	12 gal	45.41 L
Water Pressure (min/max)	10-130 psi	69-896 Kpa
Drain Diameter (O.D.)	3"	7.62 cm
Floor to Center of Drain	8"	20.3 cm

## INSTALLATION

Net Weight	1153 lbs	523 kg
Clearance Between Machines	1/2" (min)	1.27 cm
Clearance Behind Machines	24" (min)	60.96 cm
Concrete Thickness	8"	20.3 cm



**DEXTER**  
LAUNDRY

### Dexter Laundry, Inc.

2211 W. Grimes, Fairfield, Iowa 52556

[www.dexterlaundry.com](http://www.dexterlaundry.com)

1-800-524-2954

© 2007, Dexter Laundry, Inc.

Dexter reserves the right to change features or specifications without notice.



Convenient Soap Dispenser



Easy Programming



Large Loading Door



Heavy Duty Construction