



**DEXTER**  
LAUNDRY

## On-Premise Maxi-Load T-600 Washer

(Model WCVD40HCS-12)



## On-Premise Maxi-Load T-600 Washer

Dexter washers are engineered for the laundry owner demanding greater efficiency, performance, and programming capabilities.

### Durable Design

- **Save water** with “sump free” design
- **304 Stainless Steel cylinder, outer tub, top, front, and side panels** keep Dexter washers looking good
- **Heavy-duty Sur-Coat Frame** is built like a battleship to last a lifetime
- **Over-sized bearings and seals** run smooth and add to machine life

### VFD Technology

- **Reduce installation cost** by using single or three phase power
- **Extend motor life** by ramping current inrush
- **Save electricity** with lower running amperage draw
- **Lower electricity demand** by eliminating spike usage

### 100 G-Force Extraction

- **Save drying energy** with 100 G-Force washers that remove more water
- **Enhance customer turnover** with better washer and dryer performance
- **Achieve consistent results** throughout all washer sizes

### Powerful Controls

- **Palm OS®** with built-in infrared port
- **Save programming time** using a handheld computer running optional Palm OS® software
- **Easily customize** cycles, water temperatures, supply inputs and more

### Customer Friendly Design

- **Large, easy to use door** for convenient loading and unloading
- **Easily connected** to automatic supply injection systems
- **Easy-to-read digital display** including cycle time remaining information
- **Soft touch cycle selection buttons** with temperature icons
- **Ultra-quiet machine operation** improves the laundry environment



# T-600 Washer OPL Specifications

## CAPACITY

Load Size		Maxi-Load	
Dry Weight Capacity	40 lbs.		18 kg
Cylinder Diameter	25"		63.5 cm
Cylinder Depth	21.13"		53.7 cm
Cylinder Volume	6 cu ft		170.1 dm <sup>3</sup>

## DIMENSIONS

Cabinet Height	49.75"		126.37 cm
Cabinet Width	29.88"		75.88 cm
Overall Depth	36"		91.44 cm
Floor to Door Bottom	16"		40.64 cm
Door Opening	15.25"		38.74 cm

## WASHING/EXTRACTION

High Extract Speed	100 G-Force		532 RPM
Intermediate Extract Speed	60 G-Force		412 RPM
Washing Speed		50 RPM	
Motor Size	2 HP		1.5 Kw

## ELECTRICAL

Electrical Phase		Single or Three	
Electrical Voltage (60 Hz)		208-240 volts	
Electrical Running (Amps)		6.2	
Circuit Protection (Amps)		15 amp	
Electrical Wire Size		14 gauge	
Electrical Service (Single Phase)		2 wire + ground	
Electrical Service (Three Phase)		3 wire + ground	

## WATER

Water Inlet Size	3/4"		19mm
Water Flow Rate (per minute)	9 gal		34.06 L
Water Pressure (min/max)	30-120 psi		207-827 Kpa
Drain Diameter (O.D.)	3"		7.62 cm
Floor to Center of Drain	5"		12.7 cm

## INSTALLATION

Net Weight	631 lbs		286.2 kg
Clearance Between Machines	1/2" (min)		1.27 cm
Clearance Behind Machines	24" (min)		60.96 cm
Concrete Thickness	6" (min)		15.24 cm



**DEXTER**  
LAUNDRY

**Dexter Laundry, Inc.**  
2211 W. Grimes, Fairfield, Iowa 52556  
www.dexterlaundry.com  
1-800-524-2954

© 2007, Dexter Laundry, Inc.  
Dexter reserves the right to change features or specifications without notice.



Convenient Soap Dispenser



Easy Programming



Large Loading Door



Heavy Duty Construction